

LENO jut-out

semi-recessed / surface system

051-8216537J 051-8920188



Project / Type

Notes

Count / Date



**General**  
Ceiling / Wall , Semi-Recessed<sup>1</sup>-Surface<sup>2</sup>  
black , RAL9005 <sup>3</sup>  
1930 lm/m  
front IP40<sup>1</sup>-IP20<sup>2</sup> , back IP20  
3520 lm


**LED**  
3000 K  
CRI ≥ 80  
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam ≤ 3 SDCM  
MR 0.54  
MDER 0.49

**Optical**  
Jut-Out  
PstLM ≤ 1.0 <sup>4</sup>  
SVM ≤ 0.4 <sup>4</sup>


**Electrical**  
DALI-2  
28.6 W  
PC1 220-240V  
123 lm/W  
1 DALI Addr.  
16 W/m

**Physical**  
length 1830 mm  
width 89 mm  
height 38 mm  
4.3 kg

Light distribution



Product drawing



**Cutout**  
length 1843 mm  
width 70 mm  
min. ceiling thickness 12.5 mm  
recessed depth 13 mm

<sup>1</sup> semi-recessed <sup>2</sup> surface <sup>3</sup> RAL code  
<sup>4</sup> Value of containing product at full load (undimmed)

Installation instructions

