

# MOVE IT 25 S track

indirect

050-741251P



Project / Type \_\_\_\_\_  
Notes \_\_\_\_\_  
Count / Date \_\_\_\_\_



## General

Ceiling | Suspended \_\_\_\_\_  
white | RAL 9016 <sup>1</sup> \_\_\_\_\_  
Inner colour black \_\_\_\_\_  
IP20 \_\_\_\_\_  
648 lm \_\_\_\_\_  
1330 lm/m \_\_\_\_\_  
optical inset 139 lm/W <sup>2</sup> \_\_\_\_\_

## LED

3000 K \_\_\_\_\_  
CRI ≥ 90 \_\_\_\_\_  
L80 / 50000 h \_\_\_\_\_  
initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
R<sub>g</sub>: 99 | R<sub>r</sub>: 91 | R<sub>(1-15)</sub>: 89 \_\_\_\_\_  
MR 0.61 | MDER 0.55 \_\_\_\_\_

## Optical

PstLM ≤ 1.0 <sup>3</sup> | SVM ≤ 0.4 <sup>3</sup> \_\_\_\_\_

## Electrical


non DIM \_\_\_\_\_  
PC3 | 48 V \_\_\_\_\_  
fixture 6.2 W \_\_\_\_\_  
optical inset 4.7 W \_\_\_\_\_  
13 W/m \_\_\_\_\_

## Physical


length 620 mm | width 31 mm | height 31 mm \_\_\_\_\_  
0.5 kg \_\_\_\_\_

Thin extruded aluminium profile with 31mm height and 28mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power rail profile for supply voltage feed; surface white powder coated; Inner colour anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately; light source not replaceable;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

