

# LENO jut-out

semi-recessed / surface system

051-8214637J 051-8920128



Project / Type


Notes

Count / Date




Low profile recessed mounted luminaire, 15 mm visible height or low profile surface mounted luminaire, 28 mm total height; converter integrated into luminaire housing; suitable for wall or ceiling mounting; suitable for installation in primed or exposed concrete, in plasterboard constructions and in plastered walls or ceilings; for continuous lighting systems; surface black powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light directed downward through LGP (LIGHT GUIDING PRISM) body and high efficiency reflector; HPO (High Performance Opal) cover for uniform illumination; jut-out cover; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



↑ IP20

↓ IP40

220-240V

no sun

X-PERT

## General

Ceiling / Wall , Surface<sup>1</sup>-Semi-Recessed<sup>2</sup>

black , RAL9005 <sup>3</sup>

2040 lm/m

front IP20<sup>1</sup>-IP40<sup>2</sup> , back IP20

2490 lm

## LED

4000 K

CRI  $\geq 80$

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam  $\leq 3$  SDCM

MR 0.72

MDER 0.66

## Optical

Jut-Out

PstLM  $\leq 1.0$  <sup>4</sup>

SVM  $\leq 0.4$  <sup>4</sup>

## Electrical

DALI-2

19.1 W

PC1 220-240V

130 lm/W

1 DALI Addr.

16 W/m

## Physical

length 1221 mm

width 89 mm

height 38 mm

3 kg

## Cutout

length 1234 mm

width 70 mm

min. ceiling thickness 12.5 mm

recessed depth 13 mm

<sup>1</sup> surface <sup>2</sup> semi-recessed <sup>3</sup> RAL code  
<sup>4</sup> Value of containing product at full load (undimmed)

## Installation instructions



# LENO jut-out

semi-recessed / surface system  
051-8214637J 051-8920128



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B13	24
B16	30
B20	37
C10	31
C13	40
C16	51
C20	62

## Components

### INSTALLATION CHANNEL

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
1221 mm	jet black	1221-89-28	051-8920128



### Mounting accessories

#### END CAPS

COLOUR	ARTICLE NUMBER(S)
pure white	051-8992217
jet black	051-8992218



### Mounting accessories

#### LINEAR CONNECTOR

TYPE	ARTICLE NUMBER(S)
1 pair	051-8992110
10 pairs	051-8992110:10



#### POWER FEEDER CONNECTOR

ARTICLE NUMBER(S)
051-8992330



### Other accessories

#### DISMOUNTING TOOL

TYPE	ARTICLE NUMBER(S)
vacuum cup	086-30000

