

MOVE IT 25 S track corner

indirect
050-7411018



Project / Type


Notes

Count / Date




90° angle connector; Thin extruded aluminium profile with 31mm height and 28mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately; light source not replaceable;

Light distribution



Product drawing



General

Ceiling | Suspended

black | RAL 9005 ¹

IP20

1550 lm

15200 lm/m

optical inset 139 lm/W ²

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 | R_f: 91 | R₍₁₋₁₅₎: 89

MR 0.61 | MDER 0.55

Optical

PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical

non DIM

PC3 | 48 V

fixture 13.1 W

optical inset 11.2 W

129 W/m

Physical

length 637 mm | width 610 mm | height 31 mm

1 kg

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator



MOVE IT 25 S track corner

indirect
050-7411018



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.87	0.83	0.8
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

CABLE SUSPENSION

COLOUR	ARTICLE NUMBER(S)
chrome	005-2152110
black	005-2152118



CANOPY square

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
traffic white	90-90-22	005-2311717
jet black	90-90-22	005-2311718



MOVE IT 25 S track corner

indirect

050-7411018



Project / Type

Notes

Count / Date

Electrical accessories

MECHANICAL LINEAR CONNECTOR

COLOUR

chrome

black

ARTICLE NUMBER(S)

050-2011310

050-2011318



MECHANICAL & ELECTRICAL LINEAR CONNECTOR

ARTICLE NUMBER(S)

050-2031230



POWER SUPPLY INTRACK

TYPE

incl. cable 2000 mm

incl. cable 2000 mm

L-W-H (MM)

403-26-46

403-26-46

ARTICLE NUMBER(S)

050-2071038

050-2071138



POWER SUPPLY EXTERNAL

L-W-H (MM)

163-43-32

350-30-18

350-30-18

400-40-22

252-90-44

ARTICLE NUMBER(S)

002-62133

002-62134

002-62135

002-62139

002-60320



DALI-2 SELV DEVICE

TYPE

control unit

L-W-H (MM)

212-37-26

ARTICLE NUMBER(S)

050-2061130



ESSENTIAL SENSOR

TYPE

brightness & presence

L-W-H (MM)

125-28-45

ARTICLE NUMBER(S)

050-2063178



POWER FEEDER UNIT

L-W-H (MM)

78-28-6

ARTICLE NUMBER(S)

050-2024130



Electrical accessories

POWER FEEDER UNIT

L-W-H (MM)

78-28-6

78-28-6

ARTICLE NUMBER(S)

050-2020110

050-2020130



MOVE IT 25 S track corner

indirect
050-7411018



Project / Type

Notes

Count / Date

Optional electrical accessories

DIN RAIL POWER SUPPLY PRO

L-W-H (MM)	ARTICLE NUMBER(S)
60-125-100	005-6220110
100-125-120	005-6220210



DIN RAIL POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



Optical accessories

BLIND COVER

COLOUR	ARTICLE NUMBER(S)
jet black	050-7004008
jet black	050-7008008
jet black	050-7009008



END CAPS

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
1 pair	jet black	31-31-3	050-7310008
1 pair	gold / black	31-31-3	050-731000G
1 pair	white / black	31-31-3	050-731000P
1 pair	special colours	31-31-3	050-731000X

