



LENO

semi-recessed


EN Low profile recessed mounted luminaire, 15 mm visible height; suitable for wall or ceiling mounting; suitable for installation in primed or exposed concrete, in plasterboard constructions and in plastered walls or ceilings; surface powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering

DE Extrem flache Einbauleuchte mit 15 mm sichtbarer Höhe; geeignet für die Wand- oder Deckenmontage; geeignet für den Einbau in gespachtelten Beton oder Sichtbeton, in Gipskartonkonstruktionen und in verputzten Wänden oder Decken; Oberfläche pulverbeschichtet; absturzesicherer Lichteinsatz aus stranggepresstem Aluminiumprofil werkzeuglos mittels Magnethalter in Kanal einsetzbar; seitlich eingekoppeltes Licht durch LGP-Body (Light-Guiding-Prism) und hocheffizientem Reflektor nach unten gelenkt; homogen ausgeleuchtete, satinierte (bündig oder herausragend) oder mikroprismatische Abdeckung aus PMMA; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, 3 SDCM
 up to 137 lm/W
 L90 @ 50 000 h
 DALI-2
 opal, microprismatic (UGR ≤ 19),
 jut-out

Types



Colours




Light distributions



DiiA® standards
 251, 252, 253



system
 solution (p. 870)



microprismatic
 UGR ≤ 19



quick
 installation

Order options

COLOUR TEMPERATURE	☐☐
3000K	5
4000K	6

CONTROL

DALI-2	
--------	--

MATERIAL COLOUR

☐ traffic white RAL 9016	7
● jet black RAL 9005	8

LIGHT OPTIC COVER

opal high performance	H
microprismatic (UGR ≤ 19)	G
jut-out	J


Options on request

COLOUR RENDERING INDEX

CRI ≥ 90



LENO semi-recessed



LUMINAIRE

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
10.8W	3000K	1230lm	618	0 5 1 - 8 5 1 2 :: 3 ☐☐
	4000K	1300lm		
19.1W	3000K	2450lm	1226	0 5 1 - 8 5 1 4 :: 3 ☐☐
	4000K	2600lm		
28.6W	3000K	3680lm	1835	0 5 1 - 8 5 1 6 :: 3 ☐☐
	4000K	3890lm		
38W	3000K	4900lm	2443	0 5 1 - 8 5 1 8 :: 3 ☐☐
	4000K	5190lm		


Accessories



DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0

Technical data



LENO semi-recessed, 19.1W, 4000K

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

