



| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |



| | | | |
|------------------|----------|----|--------|
| ↑ IP20 ↓ IP40 | 220-240V | ☀️ | X-PERT |
|------------------|----------|----|--------|

| |
|--------------------------------|
| General |
| Ceiling / Wall , Semi-Recessed |
| black , RAL9005 ¹ |
| 1920 lm/m |
| front IP40 , back IP20 |
| 2350 lm |

| |
|---------------------------------|
| LED |
| 3000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| photobio. safety RG 0 - no Risk |
| initial MacAdam ≤ 3 SDCM |
| MR 0.54 |
| MDER 0.49 |

| |
|--------------------------|
| Optical |
| Jut-Out |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |


| |
|--------------|
| Electrical |
| DALI-2 |
| 19.1 W |
| PC1 220-240V |
| 123 lm/W |
| 1 DALI Addr. |
| 16 W/m |

| |
|----------------|
| Physical |
| length 1226 mm |
| width 89 mm |
| height 38 mm |
| 3.7 kg |

| |
|--------------------------------|
| Cutout |
| length 1234 mm |
| width 70 mm |
| min. ceiling thickness 12.5 mm |
| recessed depth 13 mm |

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions

