

# LENO microprismatic

semi-recessed / surface system

051-8214537G 051-8920127



Project / Type

Notes

Count / Date



## General

Ceiling / Wall , Semi-Recessed<sup>1</sup>-Surface<sup>2</sup>

white , RAL9010 <sup>3</sup>

1900 lm/m

front IP40<sup>1</sup>-IP20<sup>2</sup> , back IP20

2320 lm

## LED

3000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.54

MDER 0.49

## Optical

Microprismatic

UGR < 19

PstLM ≤ 1.0 <sup>4</sup>

SVM ≤ 0.4 <sup>4</sup>

## Electrical

DALI-2

19.1 W

PC1 220-240V

121 lm/W

1 DALI Addr.

16 W/m

## Physical

length 1221 mm

width 89 mm

height 28 mm

3 kg

## Cutout

length 1234 mm


width 70 mm

min. ceiling thickness 12.5 mm


recessed depth 13 mm

<sup>1</sup> semi-recessed <sup>2</sup> surface <sup>3</sup> RAL code  
<sup>4</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions

