



Project / Type

Notes

Count / Date



General
Ceiling / Wall , Semi-Recessed
white , RAL9010 ¹
2120 lm/m
front IP40 , back IP20
1300 lm

LED
4000 K
CRI ≥ 80
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
MR 0.72
MDER 0.66

Optical
High Performance Opal
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical
DALI-2
10.8 W
PC1 220-240V
120 lm/W
1 DALI Addr.
18 W/m

Physical
length 618 mm
width 89 mm
height 28 mm
2.15 kg

Cutout
length 626 mm
width 70 mm
min. ceiling thickness 12.5 mm
recessed depth 13 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Low profile recessed mounted luminaire, 15 mm visible height; converter integrated into luminaire housing; suitable for installation in primed or exposed concrete, in plasterboard constructions and in plastered walls or ceilings; suitable for wall or ceiling mounting; surface white powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light directed downward through LGP (LIGHT GUIDING PRISM) body and high efficiency reflector; HPO (High Performance Opal) cover for uniform illumination; flush cover; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection from below IP40 (from above IP20); PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing

