

# MOVE IT 25 track indirect

050-740251P



Project / Type

Notes

Count / Date



Extruded aluminium profile with 28mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power rail profile for supply voltage feed; surface white; powder coated / anodised; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V; accessories are listed separately; light source not replaceable;



### General

Ceiling , Suspended

white , RAL9016/RAL9005 <sup>1</sup>

Inner colour black

1330 lm/m

IP20

648 lm

### LED

3000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

### Electrical

non DIM

6.2 W

PC3 48V

105 lm/W

13 W/m

### Physical


length 620 mm

width 31 mm

height 60 mm

0.2 kg

### Light distribution



### Product drawing



<sup>1</sup> RAL code

### Installation instructions



### Lighting calculator

