



| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |



General

| |
|------------------------------|
| Ceiling / Wall , Recessed |
| white , RAL9016 ¹ |
| 2040 lm/m |
| front IP40 , back IP20 |
| 4970 lm |

LED

| |
|---------------------------------|
| 4000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| photobio. safety RG 0 - no Risk |
| initial MacAdam ≤ 3 SDCM |
| MR 0.72 |
| MDER 0.66 |

Optical

| |
|--------------------------|
| Jut-Out |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|--------------|
| DALI-2 |
| 38 W |
| PC2 220-240V |
| 131 lm/W |
| 1 DALI Addr. |
| 16 W/m |

Physical


| |
|----------------|
| trim |
| length 2454 mm |
| width 102 mm |
| height 23 mm |
| 5.7 kg |

Cutout


| |
|---|
| length 2444 mm |
| width 92 mm |
| min. ceiling thickness 12.5 mm |
| max. ceiling thickness 25 mm |
| recessed depth 58 mm |
| recessed depth: 12.5 mm (ceiling) + 45 mm (converter) |

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions

