

MOVE IT 25 track corner indirect

050-7401018



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Suspended _____

black | RAL 9005 ¹ _____

IP20 _____

1550 lm _____

1730 lm/m _____

optical inset 70 lm/W ² _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 | R_f: 91 | R₍₁₋₁₅₎: 89 _____

MR 0.61 | MDER 0.55 _____

Electrical

non DIM _____

PC3 | 48 V _____

fixture 13.1 W _____

optical inset 11.2 W _____

15 W/m _____

Physical


length 637 mm | width 610 mm | height 60 mm _____

1.4 kg _____


90° angle connector; Extruded aluminium profile with 28mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately; light source not replaceable;

¹ RAL code ² incl. consideration of optical losses

Light distribution



Product drawing



Installation instructions



Lighting calculator

