



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Surface
 white , RAL 9010 ¹
 IP20
 3520 lm
 1930 lm/m

LED

3000 K
 CRI ≥ 80
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 MR 0.54
 MDER 0.49

Optical

Jut-Out
 opal (lambertsch)
 PstLM ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical


DALI-2
 220-240 V
 system 28.6 W
 system 123 lm/W³
 PC1
 1 DALI Addr.
 16 W/m

Physical


length 1835 mm
 width 89 mm
 height 38 mm
 4.4 kg

Extremely flat surface mounted luminaire made of extruded aluminium profile with 28mm total height; converter integrated into luminaire housing; suitable for wall or ceiling mounting; surface white powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light directed downward through LGP (LIGHT GUIDING PRISM) body and high efficiency reflector; HPO (High Performance Opal) cover for uniform illumination; jut-out cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

