


LENO microprismatic

trim


051-8416637G



Project / Type
Notes
Count / Date



Low profile recessed channel, height 14 mm; suitable for installation in 12.5mm ceilings, with trim; suitable for wall or ceiling mounting; surface traffic white powder coated; easy mounting without need to cut the substructure; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light directed downward through LGP (LIGHT GUIDING PRISM) body and high efficiency reflector; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; UGR ≤ 19 ; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; internal wiring in light halogen free; incl. external converter for ceiling insertion; DALI-2 control; light source not replaceable; control gear replaceable by an authorized professional;



General

Ceiling / Wall Recessed
traffic white RAL 9016
front IP40 back IP20
3680 lm
2010 lm/m

LED

4000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.72 MDER 0.66

Optical

Microprismatic microprismatic
UGR ≤ 19
PstLM ≤ 1.0 ¹ SVM ≤ 0.4 ¹


Electrical

DALI-2 1 DALI Addr.
PC2 220-240 V
system 28.6 W
system 129 lm/W ²
16 W/m


Physical

trim
length 1846 mm width 102 mm height 14 mm
4.2 kg

Light distribution



Product drawing



Cutout

length 1836 mm width 92 mm
min. ceiling thickness 12.5 mm max. ceiling thickness 25 mm
recessed depth 58 mm
recessed depth: 12.5 mm (ceiling) + 45 mm (converter)

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

