

MOVE IT 25 S track

050-731803X



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours , special colours/RAL9005 ¹

Inner colour black

IP20

Electrical

DALI-2 single control

PC3 48V

Physical

length 2420 mm

width 31 mm

height 31 mm

1.72 kg

¹ RAL code

Installation instructions



Thin extruded aluminium profile with 31mm height and 28mm width groove; for wall-/ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with integrated power track profile for take off of supply voltage and DALI signal; surface special colours; powder coated / anodised; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V; accessories are listed separately;

Product drawing



MOVE IT 25 S track

050-731803X



Project / Type

Notes

Count / Date

Mounting accessories

CEILING FASTENER

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 10 | 050-204117 |
| jet black | 10 | 050-204118 |



CABLE SUSPENSION

| COLOUR | ARTICLE NUMBER(S) |
|--------|-------------------|
| chrome | 005-215210 |
| black | 005-215218 |



CANOPY

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|---------------|------------|-------------------|
| traffic white | 90-90-22 | 005-231177 |
| jet black | 90-90-22 | 005-231178 |



Electrical accessories

MECHANICAL LINEAR CONNECTOR

| COLOUR | ARTICLE NUMBER(S) |
|--------|-------------------|
| chrome | 050-201130 |
| black | 050-201138 |



MECHANICAL LINEAR CONNECTOR SURFACE

| ARTICLE NUMBER(S) |
|-------------------|
| 050-201140 |



MECHANICAL & ELECTRICAL LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 050-2031230 |



MOVE IT 25 S track

050-731803X



Project / Type

Notes

Count / Date

Electrical accessories

POWER FEEDER UNIT

| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
|---------|------------|-------------------|
| non DIM | 78-28-6 | 050-2022110 |
| DALI-2 | 78-28-6 | 050-2022130 |
| non DIM | 78-28-6 | 050-2024110 |



POWER SUPPLY SURFACE

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|---------------|------------|-------------------|
| traffic white | 305-144-54 | 050-2055117 |
| jet black | 305-144-54 | 050-2055118 |
| traffic white | 305-144-54 | 050-2055137 |
| jet black | 305-144-54 | 050-2055138 |
| traffic white | 455-104-40 | 050-2055417 |
| jet black | 455-104-40 | 050-2055418 |
| traffic white | 455-104-40 | 050-2055437 |
| jet black | 455-104-40 | 050-2055438 |
| traffic white | 455-104-40 | 050-2055217 |
| jet black | 455-104-40 | 050-2055218 |
| traffic white | 455-104-40 | 050-2055237 |
| jet black | 455-104-40 | 050-2055238 |
| traffic white | 455-104-40 | 050-2055517 |
| jet black | 455-104-40 | 050-2055518 |
| traffic white | 455-104-40 | 050-2055537 |
| jet black | 455-104-40 | 050-2055538 |
| traffic white | 305-144-54 | 050-2055317 |
| jet black | 305-144-54 | 050-2055318 |
| traffic white | 305-144-54 | 050-2055337 |
| jet black | 305-144-54 | 050-2055338 |



POWER SUPPLY EXTERNAL

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 163-43-32 | 002-62133 |
| 350-30-18 | 002-62134 |
| 350-30-18 | 002-62135 |
| 400-40-22 | 002-62139 |
| 252-90-44 | 002-60320 |



DALI-2 SELV DEVICE

| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------------|------------|-------------------|
| control unit | 213-37-25 | 050-2061130 |



DALI DAYLIGHT & MOVEMENT SENSOR

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 125-28-45 | 050-2063178 |



Optional electrical accessories

DIN RAIL POWER SUPPLY PRO

| L-W-H (MM) | ARTICLE NUMBER(S) |
|-------------|-------------------|
| 60-125-100 | 005-6220110 |
| 100-125-120 | 005-6220210 |



DIN RAIL POWER SUPPLY

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 72-90-63 | 005-6520210 |



['050-731803X'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

05.05.2024

MOVE IT 25 S track

050-731803X



Project / Type

Notes

Count / Date

Optical accessories

BLIND COVER

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|---------|-----------|-------------------|
| 1217 mm | jet black | 050-7004008 |
| 2417 mm | jet black | 050-7008008 |
| 3622 mm | jet black | 050-7009008 |



END CAPS

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|-----------------|------------|-------------------|
| 1 pair | jet black | 31-31-3 | 050-7310008 |
| 1 pair | gold / black | 31-31-3 | 050-731000G |
| 1 pair | white / black | 31-31-3 | 050-731000P |
| 1 pair | special colours | 31-31-3 | 050-731000X |

