

LENO microprismatic

semi-recessed / surface system

051-8218637G 051-8920248



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Surface¹-Semi-Recessed²

black , RAL9005 ³

2010 lm/m

front IP20¹-IP40² , back IP20

4910 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

Optical

Microprismatic

UGR < 19

PstLM ≤ 1.0 ⁴

SVM ≤ 0.4 ⁴

Electrical

DALI-2

38 W

PC1 220-240V

129 lm/W

1 DALI Addr.

16 W/m

Physical

length 2438 mm

width 89 mm

height 28 mm

5.5 kg

Cutout

length 2451 mm


width 70 mm

min. ceiling thickness 12.5 mm


recessed depth 13 mm

¹ surface ² semi-recessed ³ RAL code
⁴ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



LENO microprismatic

semi-recessed / surface system

051-8218637G 051-8920248



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a Room Surface Maintenance Factor		
MF	Maintenance Factor		LLMF Lamp Lumens Maintenance Factor		
LMF ^a	Luminaire Maintenance Factor		LSF Lamp Survival Faktor		

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B13	24
B16	30
B20	37
C10	31
C13	40
C16	51
C20	62

Components

INSTALLATION CHANNEL

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
2438 mm	jet black	2438-89-28	051-8920248



Mounting accessories

END CAPS

COLOUR	ARTICLE NUMBER(S)
pure white	051-8992217
jet black	051-8992218



Mounting accessories

LINEAR CONNECTOR

TYPE	ARTICLE NUMBER(S)
1 pair	051-8992110
10 pairs	051-8992110:10



POWER FEEDER CONNECTOR

ARTICLE NUMBER(S)
051-8992330



Other accessories

DISMOUNTING TOOL

TYPE	ARTICLE NUMBER(S)
vacuum cup	086-30000

