

# LENO jut-out

semi-recessed / surface system

051-8218537J 051-8920248



Project / Type


Notes

Count / Date




Low profile recessed mounted luminaire, 15 mm visible height or low profile surface mounted luminaire, 28 mm total height; converter integrated into luminaire housing; suitable for wall or ceiling mounting; suitable for installation in primed or exposed concrete, in plasterboard constructions and in plastered walls or ceilings; for continuous lighting systems; surface black powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light directed downward through LGP (LIGHT GUIDING PRISM) body and high efficiency reflector; HPO (High Performance Opal) cover for uniform illumination; jut-out cover; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection from below IP40 (from above IP20); PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling / Wall | Semi-Recessed<sup>1</sup>-Surface<sup>2</sup>

black | RAL 9005<sup>3</sup>

front IP40<sup>1</sup>-IP20<sup>2</sup> | back IP20

4700 lm

1930 lm/m

jet black

## LED

3000 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.54 | MDER 0.49

## Optical

Jut-Out | opal (lambertsch)

PstLM  $\leq 1.0$ <sup>1 2 4</sup> | SVM  $\leq 0.4$ <sup>1 2 4</sup>

## Electrical

DALI-2 | 1 DALI Addr.

PC1 | 220-240 V

system 38 W

system 124 lm/W<sup>5</sup>

16 W/m

## Physical

length 2438 mm | width 89 mm | height 38 mm

5.5 kg

## Cutout

length 2451 mm | width 70 mm

min. ceiling thickness 12.5 mm

recessed depth 13 mm

<sup>1</sup> semi-recessed <sup>2</sup> surface <sup>3</sup> RAL code  
<sup>4</sup> Value of containing product at full load (undimmed)  
<sup>5</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions

