

MOVE IT 45 track indirect

050-7434538



Project / Type

Notes

Count / Date



Extruded aluminium profile with 45mm width groove; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; indirect light component covered with opal lens cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V; sound absorbing accessories for installation in the MOVE IT suspended system available; accessories are listed separately; light source not replaceable;



General

Ceiling , Suspended

black , RAL9005 ¹

1670 lm/m

IP20

1810 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 91 , R_{f(1-15)}: 89

MR 0.61

MDER 0.55

Electrical

DALI-2 single control

15.3 W

PC3 48V

118 lm/W

1 DALI Addr.

14 W/m

Physical

length 1220 mm


width 48 mm

height 60 mm


1.64 kg

¹ RAL code

Light distribution



Product drawing



Installation instructions



Lighting calculator

