

TULA micro suspended

MOVE IT 25 / 25 S / 45

050-1815437M



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

white , RAL 9016 ¹ _____

IP20 _____

972 lm _____

optical inset 81 lm/W² _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 96 , R_r: 90 , R_{t(1-15)}: 88 _____

MR 0.55 _____

MDER 0.5 _____

Optical

medium _____

beam angle 25° _____

PstLM ≤ 1.0 ³ _____

SVM ≤ 0.4 ³ _____

Electrical

DALI-2 _____

48 V _____

fixture 14.1 W _____

optical inset 12.0 W _____

PC3 _____

1 DALI Addr. _____

Physical

diameter 47 mm _____


height 500 mm _____

0.7 kg _____

2000 mm with hook _____

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	4200	0.44
2	1050	0.89
3	470	1.33
4	260	1.78
5	170	2.22

Product drawing



Installation instructions



Lighting calculator

