

# MICROPRISM UGR < 22

MOVE IT 45

050-3244638P



Project / Type

Notes

Count / Date



## General

Ceiling / Wall , Track

black , RAL9005 <sup>1</sup>

IP20

3300 lm

## LED

4000 K

CRI ≥ 90

L85 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 98 , R<sub>r</sub>: 90 , R<sub>r(1-15)</sub>: 88

MR 0.76

MDER 0.69

## Optical

Microprismatic

## Electrical

DALI-2 single control

51 W

PC3 48V

65 lm/W

1 DALI Addr.

## Physical

length 1205 mm

width 43 mm

height 48 mm

1,21 kg


<sup>1</sup> RAL code

## Installation instructions



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; completely homogeneously illuminated, microprismatic PMMA cover; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

## Light distribution



## Product drawing

