

# MOVE IT 25 S trimless track

050-7218038



Project / Type


Notes

Count / Date



Thin extruded aluminium profile with 31mm height and 28mm width groove; for trimless installation in plasterboard ceilings; suitable for wall or ceiling mounting; suitable for ceiling thickness of 12.5 mm; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately;

## Product drawing



### General

Ceiling | Recessed

black | RAL 9005 <sup>1</sup>

IP20

### Electrical

DALI-2

PC3 | 48 V

### Physical

length 2417 mm | width 105 mm | height 31 mm

2.74 kg

### Cutout

length 2421 mm | width 62 mm

recessed depth 80 mm

<sup>1</sup> RAL code

## Installation instructions



[‘050-7218038’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)