

MOVE IT 25 S trimless track

050-7218018



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

black , RAL 9005 ¹

IP20

Electrical

non DIM

48 V

PC3

Physical

length 2417 mm

width 105 mm

height 31 mm

2.72 kg

Cutout

length 2421 mm

width 62 mm

recessed depth 80 mm

¹ RAL code

Thin extruded aluminium profile with 31mm height and 28mm width groove; for trimless installation in plasterboard ceilings; suitable for wall or ceiling mounting; suitable for ceiling thickness of 12.5 mm; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately;

Product drawing



Installation instructions



MOVE IT 25 S trimless track

050-7218018



Project / Type	
Notes	
Count / Date	

Electrical accessories

LINEAR CONNECTOR

L-W-H (MM)	ARTICLE NUMBER(S)
100-28-6	050-2031130



LINEAR CONNECTOR FLEXIBLE

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
non DIM	78-28-6	050-2032110
DALI-2	78-28-6	050-2032130



MECHANICAL LINEAR CONNECTOR SET

ARTICLE NUMBER(S)
050-2011110



Electrical accessories

POWER FEEDER UNIT

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
non DIM	78-28-6	050-2020110
DALI-2	78-28-6	050-2020130
DALI-2	78-28-6	050-2024130



POWER SUPPLY INTRACK

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
100 W incl. cable 2000 mm	403-26-46	050-2071038
150 W incl. cable 2000 mm	403-26-46	050-2071138



POWER SUPPLY EXTERNAL

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
60 W	163-43-32	002-62133
100 W	350-30-18	002-62134
150 W	350-30-18	002-62135
250 W	400-40-22	002-62139
320 W	252-90-44	002-60320



Optional electrical accessories

DIN RAIL POWER SUPPLY PRO

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
240 W	60-125-100	005-6220110
480 W	100-125-120	005-6220210



DIN RAIL POWER SUPPLY

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
160 W	72-90-63	005-6520210



[050-7218018] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

04.05.2025

MOVE IT 25 S trimless track

050-7218018



Project / Type

Notes

Count / Date

Optical accessories

END CAPS

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
1 pair	54-31-2	050-7210008



BLIND COVER

TYPE	COLOUR	ARTICLE NUMBER(S)
1217 mm	jet black	050-7004008
2417 mm	jet black	050-7008008
3622 mm	jet black	050-7009008

