

MOVE IT 25 S trimless track

050-7212018



Project / Type


Notes

Count / Date



Thin extruded aluminium profile with 31mm height and 28mm width groove; for trimless installation in plasterboard ceilings; suitable for wall or ceiling mounting; suitable for ceiling thickness of 12.5 mm; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately;

Product drawing



General

Ceiling | Recessed

black | RAL 9005 ¹

IP20

Electrical

non DIM

PC3 | 48 V

Physical

length 617 mm | width 105 mm | height 31 mm

0.68 kg

Cutout

length 621 mm | width 62 mm

recessed depth 80 mm

¹ RAL code

Installation instructions



[‘050-7212018’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

MOVE IT 25 S trimless track

050-7212018



Project / Type

Notes

Count / Date

Electrical accessories

LINEAR CONNECTOR

L-W-H (MM)	ARTICLE NUMBER(S)
100-28-6	050-2031130



LINEAR CONNECTOR FLEXIBLE

L-W-H (MM)	ARTICLE NUMBER(S)
78-28-6	050-2032110
78-28-6	050-2032130



MECHANICAL LINEAR CONNECTOR SET

ARTICLE NUMBER(S)
050-2011110



Electrical accessories

POWER FEEDER UNIT

L-W-H (MM)	ARTICLE NUMBER(S)
78-28-6	050-2020110
78-28-6	050-2020130
78-28-6	050-2024130



POWER SUPPLY INTRACK

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
incl. cable 2000 mm	403-26-46	050-2071038
incl. cable 2000 mm	403-26-46	050-2071138



POWER SUPPLY EXTERNAL

L-W-H (MM)	ARTICLE NUMBER(S)
163-43-32	002-62133
350-30-18	002-62134
350-30-18	002-62135
400-40-22	002-62139
252-90-44	002-60320



Optional electrical accessories

DIN RAIL POWER SUPPLY PRO

L-W-H (MM)	ARTICLE NUMBER(S)
60-125-100	005-6220110
100-125-120	005-6220210



DIN RAIL POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



[‘050-7212018’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

MOVE IT 25 S trimless track

050-7212018



Project / Type

Notes

Count / Date

Optical accessories

END CAPS

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
1 pair	54-31-2	050-7210008



BLIND COVER

COLOUR	ARTICLE NUMBER(S)
jet black	050-7004008
jet black	050-7008008
jet black	050-7009008

