

MOVE IT 25 S trimless track

050-7212018



Project / Type


Notes

Count / Date



Thin extruded aluminium profile with 31mm height and 28mm width groove; for trimless installation in plasterboard ceilings; suitable for wall or ceiling mounting; suitable for ceiling thickness of 12.5 mm; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately;

Product drawing



General

Ceiling | Recessed

black | RAL 9005 ¹

IP20

Electrical

non DIM

PC3 | 48 V

Physical

length 617 mm | width 105 mm | height 31 mm

0.68 kg

Cutout

length 621 mm | width 62 mm

recessed depth 80 mm

¹ RAL code

Installation instructions



[‘050-7212018’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com