

MOVE IT 25 S trimless track ceiling wall


050-7211138



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Recessed

black , RAL 9005 ¹

IP20

Electrical

DALI-2 single control

48 V

PC3

Physical

length 661 mm

width 71 mm

height 661 mm

1.5 kg

Cutout


width 62 mm

recessed depth 52 mm

¹ RAL code

90° angle connector ceiling - wall; Thin extruded aluminium profile with 31mm height and 28mm width groove; for trimless installation in plasterboard ceilings; suitable for wall or ceiling mounting; suitable for ceiling thickness of 12.5 mm; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately;

Product drawing



Installation instructions



[‘050-7211138’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com