

MOVE IT 25 S trimless track corner


050-7211018



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Recessed

black , RAL 9005 ¹

IP20

Electrical

non DIM

48 V

PC3

Physical

length 672 mm

width 645 mm

height 31 mm

1.5 kg


Cutout

recessed depth 52 mm

¹ RAL code

90° angle connector; Thin extruded aluminium profile with 31mm height and 28mm width groove; for trimless installation in plasterboard ceilings; suitable for wall or ceiling mounting; suitable for ceiling thickness of 12.5 mm; with integrated power rail profile for supply voltage feed; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3; 48 V; accessories are listed separately;

Product drawing



Installation instructions



MOVE IT 25 S trimless track corner

050-7211018



Project / Type

Notes

Count / Date

Electrical accessories

LINEAR CONNECTOR

L-W-H (MM)
100-28-6

ARTICLE NUMBER(S)
050-2031130



LINEAR CONNECTOR FLEXIBLE

TYPE
non DIM
DALI-2

L-W-H (MM)
78-28-6
78-28-6

ARTICLE NUMBER(S)
050-2032110
050-2032130



MECHANICAL LINEAR CONNECTOR SET

ARTICLE NUMBER(S)
050-2011110

MECHANICAL
80

MECHANICAL
80

Electrical accessories

POWER FEEDER UNIT

TYPE
non DIM
DALI-2
DALI-2

L-W-H (MM)
78-28-6
78-28-6
78-28-6

ARTICLE NUMBER(S)
050-2020110
050-2020130
050-2024130



POWER SUPPLY INTRACK

TYPE
100 W | incl. cable 2000 mm
150 W | incl. cable 2000 mm

L-W-H (MM)
403-26-46
403-26-46

ARTICLE NUMBER(S)
050-2071038
050-2071138



POWER SUPPLY EXTERNAL

TYPE
60 W
100 W
150 W
250 W
320 W

L-W-H (MM)
163-43-32
350-30-18
350-30-18
400-40-22
252-90-44

ARTICLE NUMBER(S)
002-62133
002-62134
002-62135
002-62139
002-60320



Optional electrical accessories

DIN RAIL POWER SUPPLY PRO

TYPE
240 W
480 W

L-W-H (MM)
60-125-100
100-125-120

ARTICLE NUMBER(S)
005-6220110
005-6220210



DIN RAIL POWER SUPPLY

TYPE
160 W

L-W-H (MM)
72-90-63

ARTICLE NUMBER(S)
005-6520210



[050-7211018] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

04.05.2025

MOVE IT 25 S trimless track corner

050-7211018



Project / Type

Notes

Count / Date

Optical accessories

END CAPS

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
1 pair	54-31-2	050-7210008



BLIND COVER

TYPE	COLOUR	ARTICLE NUMBER(S)
1217 mm	jet black	050-7004008
2417 mm	jet black	050-7008008
3622 mm	jet black	050-7009008

