

TULA nano suspended

MOVE IT 25

050-1811517M



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL9016 ¹

IP20

732 lm

LED

3000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

Optical

medium

beam angle 24°

Electrical

non DIM

12.1 W

PC3

60 lm/W

Physical

diameter 26 mm

height 500 mm


1.1 kg

2000 mm with hook

¹ RAL code

Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 24° beam; degree of protection IP20; PC3; non-dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



medium 24°

h (m)	EO° (lx)	ø (m)
1	2990	0.43
2	750	0.85
3	330	1.28
4	190	1.71
5	120	2.13

Product drawing



Installation instructions



Lighting calculator

