

TULA nano suspended

MOVE IT 25 / 25 S / 45

050-1811437F



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL 9016 ¹

IP20

667 lm

optical inset 73 lm/W²

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{f(1-15)}: 89

MR 0.53

MDER 0.48

Optical

flood

beam angle 30°

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2

48 V

fixture 12.1 W

optical inset 9.1 W

PC3

1 DALI Addr.

Physical

diameter 26 mm

height 500 mm


0.35 kg

2000 mm with hook

¹ RAL code ² incl. consideration of optical losses

³ Value of containing product at full load (undimmed)


Light distribution



flood 30°

h (m)	E0° (lx)	ø (m)
1	1960	0.53
2	490	1.07
3	220	1.60
4	120	2.13
5	80	2.66

Product drawing



Installation instructions



Lighting calculator



TULA nano suspended

MOVE IT 25 / 25 S / 45

050-1811437F



Project / Type

Notes

Count / Date

Mounting accessories

RING TRACK MOUNTED

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	50	050-0510117
jet black	50	050-0510118



RING CEILING MOUNTED

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	50	050-0510217
jet black	50	050-0510218



Optical accessories

OVAL LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965880



SOFT LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965980



WALLWASHER LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965780

