

# TULA nano suspended

MOVE IT 25 / 25 S / 45

050-1811434M



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

chrome

IP20

691 lm

optical inset 76 lm/W<sup>1</sup>

## LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.53

MDER 0.48

## Optical

medium

beam angle 24°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

48 V

fixture 12.1 W

optical inset 9.1 W

PC3

1 DALI Addr.

## Physical

diameter 26 mm

height 500 mm


0.35 kg

2000 mm with hook

<sup>1</sup> incl. consideration of optical losses

<sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	2820	0.43
2	700	0.85
3	310	1.28
4	180	1.71
5	110	2.13

## Product drawing



## Installation instructions



## Lighting calculator

