

TULA micro suspended

MOVE IT 25

050-1715D38F



Project / Type


Notes

Count / Date



Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 46° beam; degree of protection IP20; PC3; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



flood 46°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 467 | 0.86 |
| 2 | 117 | 1.71 |
| 3 | 52 | 2.57 |
| 4 | 29 | 3.43 |
| 5 | 19 | 4.28 |

Product drawing



General

Ceiling , Suspended

black , RAL9005 ¹

IP20

290 lm

LED

tunable white

2200 K - 4000 K

CRI ≥ 90

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 88

MR 0.83

MDER 0.75

Optical

flood

beam angle 46°

Electrical

DALI-2

5.4 W

PC3

54 lm/W

Physical

diameter 47 mm

height 500 mm

0.7 kg

1500 mm

¹ RAL code

Installation instructions



Lighting calculator

