

# PAL cable 80mm suspended

MOVE IT 25  
050-1611418



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

black , RAL9005 <sup>1</sup>

IP20

475 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>{1-15}</sub>: 89

MR 0.53

MDER 0.48

Electrical

non DIM

9.1 W

PC3 48V

52 lm/W

Physical

cable 2000 mm with hook


diameter 80 mm

height 80 mm


<sup>1</sup> RAL code

Decorative glass ball pendant light inset; opal; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened, incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

