

MOVE IT 25 S  
050-1212418A



Project / Type

## Notes

Count / Date



## General

Ceiling / Wall , Track

black , RAL9005 <sup>1</sup>

IP20

829 lm

**LED**

2700 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

$R_q: 95, R_f: 92, R_{\{1-15\}}: 90$

MR 0.45

MDER 0.41

## Optical

wallwasher

## Electrical

non DIM

11.2 W

PC3 48V

74 lm/W

## Physical

length 605 mm

width 25 mm

height 20 mm

0.3 kg


<sup>1</sup> RAL code

## Installation instructions



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; with specially computed, asymmetric lens for homogeneous vertical lighting intensity; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;

## Light distribution



## Product drawing

