

TULA micro suspended

MOVE IT 25

050-0715D37M



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 21° beam; degree of protection IP20; PC3; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling , Suspended

white , RAL9016 ¹

IP20

274 lm

LED

tunable white

2200 K - 4000 K

CRI ≥ 90

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 88

MR 0.83

MDER 0.75

Optical

medium

beam angle 21°

Electrical

DALI-2

5.4 W

PC3

51 lm/W

Physical


diameter 47 mm

height 300 mm

0.7 kg

1500 mm

Light distribution



medium 21°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 1390 | 0.38 |
| 2 | 350 | 0.76 |
| 3 | 150 | 1.14 |
| 4 | 90 | 1.52 |
| 5 | 60 | 1.90 |

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

