

TULA nano suspended

MOVE IT 25 / 25 S / 45
050-1711538F



Project / Type


Notes

Count / Date



Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling | Track Suspended
black | RAL 9005 ¹
IP20
707 lm
optical inset 78 lm/W ²

LED

3000 K
CRI ≥ 90
initial MacAdam ≤ 3 SDCM
R_g: 100 | R_f: 91 | R_{1-15}: 89
MR 0.59 | MDER 0.53

Optical

flood | beam angle 30°
PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical

DALI-2 | 1 DALI Addr.
PC3 | 48 V
fixture 12.1 W
optical inset 9.1 W

Physical

diameter 26 mm | height 500 mm
0.35 kg
1500 mm

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

