

# TULA micro suspended

MOVE IT 25

050-0715538F



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



| flood 44° |          |       |
|-----------|----------|-------|
| h (m)     | EO° (lx) | ø (m) |
| 1         | 2020     | 0.82  |
| 2         | 510      | 1.64  |
| 3         | 220      | 2.45  |
| 4         | 130      | 3.27  |
| 5         | 80       | 4.09  |

## Product drawing



### General

Ceiling , Suspended

black , RAL9005 <sup>1</sup>

IP20

1090 lm

### LED

3000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 98 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.62

MDER 0.56

### Optical

flood

beam angle 44°

### Electrical

DALI-2

14.1 W

PC3

77 lm/W

1 DALI Addr.

### Physical

diameter 47 mm

height 300 mm

0.42 kg

1500 mm

<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator

