

WALL GRAZER

MOVE IT 25 S
050-1211418S



Project / Type _____
Notes _____
Count / Date _____



General

Ceiling / Wall | Track
jet black | RAL 9005 ¹
IP20
525 lm
optical inset 141 lm/W ²

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 99 | R_r: 90 | R_{t(1-15)}: 88
MR 0.53 | MDER 0.48

Optical

wall grazer
PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical


non DIM
PC3 | 48 V
fixture 5.3 W
optical inset 3.7 W

Physical

length 305 mm | width 25 mm | height 20 mm
0.15 kg

Linear light inset made of aluminium; surface anodised jet black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; with specially calculated WALL GRAZER lens for uniform accent lighting of wall surfaces and increased emphasis of the wall surface texture; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; non-dimmable; light source not replaceable;

Light distribution



Product drawing



¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions

