

OPAL HIGH PERFORMANCE

MOVE IT 25 S
050-1211418H



Project / Type

Notes

Count / Date



Linear light inset made of PMMA; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system (MOVE IT 25 S) or recessed luminaire level (MOVE IT 25); power supplied via MOVE IT system track profile; hot plug protection; completely homogeneously illuminated, satin PMMA cover; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; non-dimmable; light source not replaceable;



General

Ceiling / Wall , Track

IP20

402 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 90 , R₍₁₋₁₅₎: 88

MR 0.53

MDER 0.48

Optical

High Performance Opal

Electrical

non DIM

5.3 W

PC3 48V

76 lm/W

Physical


length 305 mm

width 25 mm


height 20 mm

0.15 kg

Light distribution



Product drawing



Installation instructions

