

OPAL HIGH PERFORMANCE

MOVE IT 25 S
050-1218L38H



Project / Type _____


Notes _____

Count / Date _____



Linear light inset made of PMMA; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system (MOVE IT 25 S) or recessed luminaire level (MOVE IT 25); power supplied via MOVE IT system track profile; hot plug protection; completely homogeneously illuminated, satin PMMA cover; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour: tunable white diodes (1800-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



Product drawing



General

Ceiling / Wall , Track _____

IP20 _____

1910 lm _____

LED

tunable white _____

1800 K - 4000 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

R_g: 98 , R_r: 90 , R_{t(1-15)}: 88 _____

MR 0.76 _____

MDER 0.69 _____

Optical

High Performance Opal _____

Electrical

DALI-2 single control _____

21.3 W _____

PC3 48V _____

90 lm/W _____

1 DALI Addr. _____

Physical

length 2405 mm _____

width 25 mm _____

height 20 mm _____

1 kg _____

Installation instructions

