

# OPAL HIGH PERFORMANCE

MOVE IT 25 S  
050-1218538H



Project / Type


Notes

Count / Date



Linear light inset made of PMMA; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system (MOVE IT 25 S) or recessed luminaire level (MOVE IT 25); power supplied via MOVE IT system track profile; hot plug protection; completely homogeneously illuminated, satin PMMA cover; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

### Light distribution



### Product drawing



### General

Ceiling / Wall , Track

IP20

3460 lm

### LED

3000 K

CRI  $\geq 90$

L80 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

### Optical

High Performance Opal

### Electrical

DALI-2 single control

43 W

PC3 48V

80 lm/W

1 DALI Addr.

### Physical

length 2405 mm

width 25 mm

height 20 mm

1 kg

### Installation instructions

