

ARY rod suspended

MOVE IT 25
050-0621D38M



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (black) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 21° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;



General

Ceiling , Track Suspended

black , RAL9005 ¹

IP20

269 lm

LED

tunable white

2200 K - 4000 K

CRI ≥ 90

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.4

MDER 0.37

Optical

medium

beam angle 21°

Electrical

DALI-2

5.4 W

PC3 48V

50 lm/W

1 DALI Addr.

Physical


rod 1500 mm with hook

diameter 47 mm

height 110 mm


0.5 kg

Light distribution



| medium 21° | | |
|------------|----------|-------|
| h (m) | EO° (lx) | ø (m) |
| 1 | 1370 | 0.38 |
| 2 | 340 | 0.76 |
| 3 | 150 | 1.14 |
| 4 | 90 | 1.52 |
| 5 | 50 | 1.90 |

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

