

ARY adjustable rod suspended


MOVE IT 25
050-053163XM



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

tilt max 90° _____

rotation 265° _____

special colours _____

IP20 _____

1090 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 96 , R_f: 89 , R₍₁₋₁₅₎: 89 _____

MR 0.84 _____

MDER 0.76 _____

Optical

medium _____

beam angle 25° _____

Electrical

DALI-2 _____

14.1 W _____

PC3 48V _____

77 lm/W _____

1 DALI Addr. _____

Physical

rod 1500 mm _____


diameter 47 mm _____

height 110 mm _____

0.45 kg _____


Decorative pendant light inset made of aluminium; surface special colours powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (special colours) 1500mm, feed in U-profile; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



| medium 25° | | | |
|------------|----------|-------|--|
| h (m) | EO° (lx) | ø (m) | |
| 1 | 4710 | 0.44 | |
| 2 | 1180 | 0.89 | |
| 3 | 520 | 1.33 | |
| 4 | 290 | 1.78 | |
| 5 | 190 | 2.22 | |

Product drawing



Installation instructions



Lighting calculator

