

ARY rod suspended

MOVE IT 25 / 25 S / 45
050-062161XM



Project / Type

Notes

Count / Date



General

Ceiling | Track Suspended

special colours

IP20

1090 lm

optical inset 91 lm/W ¹

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 | R_f: 89 | R₁₋₁₅: 89

MR 0.84 | MDER 0.76

Optical

medium | beam angle 25°

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical

non DIM

PC3 | 48 V

fixture 14.1 W

optical inset 12.0 W

Physical


rod 1500 mm with hook

diameter 47 mm | height 110 mm

0.5 kg


Decorative pendant light inset made of aluminium; surface special colours powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (special colours) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (special colours) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC3; 48 V; non-dimmable; light source not replaceable;

Light distribution



medium 25°			
h (m)	EO° (lx)	ø (m)	
1	4710	0.44	
2	1180	0.89	
3	520	1.33	
4	290	1.78	
5	190	2.22	

Product drawing



Installation instructions



Lighting calculator

