

TULA micro suspended

MOVE IT 25 / 25 S / 45

050-0815417F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

white , RAL 9016 ¹ _____

IP20 _____

1040 lm _____

optical inset 87 lm/W² _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 96 , R_r: 90 , R_{t(1-15)}: 88 _____

MR 0.55 _____

MDER 0.5 _____

Optical

flood _____

beam angle 44° _____

PstLM ≤ 1.0 ³ _____

SVM ≤ 0.4 ³ _____

Electrical

non DIM _____

48 V _____

fixture 14.1 W _____

optical inset 12.0 W _____

PC3 _____

Physical


diameter 47 mm _____

height 300 mm _____

0.45 kg _____

2000 mm with hook _____


Light distribution



flood 44°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 1930 | 0.82 |
| 2 | 480 | 1.64 |
| 3 | 210 | 2.45 |
| 4 | 120 | 3.27 |
| 5 | 80 | 4.09 |

Product drawing



¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions

Lighting calculator

