

ARY adjustable rod suspended

MOVE IT 25
050-0631D37M



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

tilt max 90° _____

rotation 265° _____

white , RAL9016 ¹ _____

IP20 _____

269 lm _____

LED

tunable white _____

2200 K - 4000 K _____

CRI ≥ 90 _____

L95 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.4 _____

MDER 0.37 _____

Optical

medium _____

beam angle 21° _____

Electrical

DALI-2 _____

5.4 W _____

PC3 48V _____

50 lm/W _____

1 DALI Addr. _____

Physical

rod 1500 mm with hook _____


diameter 47 mm _____

height 110 mm _____

0.5 kg _____


Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (white) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 21° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



medium 21°			
h (m)	EO° (lx)	ø (m)	
1	1370	0.38	
2	340	0.76	
3	150	1.14	
4	90	1.52	
5	50	1.90	

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

