

# ARY rod suspended

MOVE IT 25

050-0521D37M



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

white , RAL9016 <sup>1</sup>

IP20

269 lm

## LED

tunable white

2200 K - 4000 K

CRI ≥ 90

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.4

MDER 0.37

## Optical

medium

beam angle 21°

## Electrical

DALI-2

5.4 W

PC3 48V

50 lm/W

1 DALI Addr.

## Physical

rod 1500 mm


diameter 47 mm

height 110 mm

0.45 kg

Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (white) 1500mm, feed in U-profile; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 21° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

## Light distribution



medium 21°

h (m)	E0° (lx)	ø (m)
1	1370	0.38
2	340	0.76
3	150	1.14
4	90	1.52
5	50	1.90

## Product drawing



<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator

