

# ARY cable suspended

MOVE IT 25 / 25 S / 45  
050-0611637M



Project / Type

Notes

Count / Date



General

Ceiling | Track Suspended

white | RAL 9016 <sup>1</sup>

IP20

1090 lm

optical inset 91 lm/W <sup>2</sup>

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 96 | R<sub>f</sub>: 89 | R<sub>1-15</sub>: 89

MR 0.84 | MDER 0.76

Optical

medium | beam angle 25°

PstLM ≤ 1.0 <sup>3</sup> | SVM ≤ 0.4 <sup>3</sup>

Electrical

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 14.1 W

optical inset 12.0 W

Physical

cable 2000 mm with hook


diameter 47 mm | height 110 mm

0.4 kg

Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened, incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;


<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Light distribution



| medium 25° |          |       |
|------------|----------|-------|
| h (m)      | E0° (lx) | ø (m) |
| 1          | 4710     | 0.44  |
| 2          | 1180     | 0.89  |
| 3          | 520      | 1.33  |
| 4          | 290      | 1.78  |
| 5          | 190      | 2.22  |

## Product drawing



## Installation instructions



## Lighting calculator

