

# ARY adjustable rod suspended

MOVE IT 25

050-0631617M



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

tilt max 90°

rotation 265°

white , RAL9016 <sup>1</sup>

IP20

1090 lm

## LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 96 , R<sub>f</sub>: 89 , R<sub>(1-15)</sub>: 89

MR 0.84

MDER 0.76

## Optical

medium

beam angle 25°

## Electrical

non DIM

14.1 W

PC3 48V

77 lm/W

## Physical

rod 1500 mm with hook


diameter 47 mm

height 110 mm

0.5 kg

Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (white) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;


## Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	4710	0.44
2	1180	0.89
3	520	1.33
4	290	1.78
5	190	2.22

## Product drawing



<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator

