

ARY cable suspended

MOVE IT 25

050-0611617F



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

white , RAL9016 ¹

IP20

1170 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 , R_f: 89 , R₍₁₋₅₎: 89

MR 0.84

MDER 0.76

Optical

flood

beam angle 44°

Electrical

non DIM

14.1 W

PC3 48V

83 lm/W

Physical

cable 2000 mm with hook

diameter 47 mm


height 110 mm

0.4 kg

¹ RAL code


Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened, incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;

Light distribution



flood 44°			
h (m)	E0° (lx)	ø (m)	
1	2170	0.82	
2	540	1.64	
3	240	2.45	
4	140	3.27	
5	90	4.09	

Product drawing



Installation instructions



Lighting calculator

