

ARY adjustable rod suspended

MOVE IT 25
050-0631538F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

tilt max 90° _____

rotation 265° _____

black , RAL9005 ¹ _____

IP20 _____

1090 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 98 , R_f: 91 , R₍₁₋₁₅₎: 89 _____

MR 0.62 _____

MDER 0.56 _____

Optical

flood _____

beam angle 44° _____

Electrical

DALI-2 _____

14.1 W _____

PC3 48V _____

77 lm/W _____

1 DALI Addr. _____

Physical

rod 1500 mm with hook _____


diameter 47 mm _____

height 110 mm _____

0.5 kg _____


Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; height adjustable U-profile pendant rod suspension (black) 1500mm, feed 2000mm (1500mm in U-profile), incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; spotlight head 265° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



flood 44°		
h (m)	EO° (lx)	ø (m)
1	2020	0.82
2	510	1.64
3	220	2.45
4	130	3.27
5	80	4.09

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

