

WALLWASHER FLUSH

MOVE IT 25

050-0212438A



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

black , RAL 9005 ¹

IP20

829 lm

optical inset 106 lm/W²

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 95 , R_r: 92 , R₍₁₋₁₅₎: 90

MR 0.45

MDER 0.41

Optical

wallwasher

P_{stLM} ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2 single control

48 V

fixture 11.2 W

optical inset 7.8 W

PC3

1 DALI Addr.

Physical

length 605 mm

width 25 mm

height 45 mm

0.4 kg

¹ RAL code ² incl. consideration of optical losses


³ Value of containing product at full load (undimmed)

Installation instructions



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; with specially computed, asymmetric lens for homogeneous vertical lighting intensity; optical attachment available as accessory; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



Product drawing

