

OPAL HIGH PERFORMANCE

MOVE IT 25
050-0211418H



Project / Type _____


Notes _____

Count / Date _____



Linear light inset made of PMMA; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; completely homogeneously illuminated, satin PMMA cover; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; non-dimmable; light source not replaceable;

Light distribution



Product drawing



General

Ceiling / Wall | Track _____

IP20 _____

451 lm _____

optical inset 121 lm/W ¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 | R_f: 90 | R_{f[1-5]}: 88 _____

MR 0.53 | MDER 0.48 _____

Optical

High Performance Opal | opal (lambertsch) _____

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ² _____

Electrical

non DIM _____

PC3 | 48 V _____

fixture 5.3 W _____

optical inset 3.7 W _____

Physical

length 305 mm | width 25 mm | height 47 mm _____

0.12 kg _____

¹ incl. consideration of optical losses
² Value of containing product at full load (undimmed)

Installation instructions

